INTIMIDATOR™ 15XP

15" Capacity Hand-Fed Chipper

The compact Intimidator 15XP is an efficient 15" capacity hydraulic-feed, drum-style hand-fed chipper with a large 37" diameter drum. Featuring a 17 -3/4" by 18-1/2" throat opening and 18-3/4" wide feed wheels, the Intimidator 15XP can easily accept large diameter trees and limby material. With its solid welded construction, proven feed system, durable components and chip throwing technologies, this chipper provides all the advantages of a hydraulicfeed drum-style chipper, yet chips like a disc with the chipping efficiency of a disc chipper. A variety of gas and diesel engine options are available, ranging from 122.5 to 165 horsepower.

- DURABLE AND POWERFUL.

 Aggressive feed systems for unmatched pulling and compressing power
- 37" diameter drum with impressive 17-34" x 18-1/2" wide throat opening
- Gas or diesel engine options available



Chip Limby Material With Limited Preparation

The Intimidator 15XP easily handles limby material with its large throat opening and Bandit's proven Slide Box Feed System. This system features powerful dual horizontal feed rollers 18-3/4" wide by 10-5/8" in diameter, powered by 32.3 CID hydraulic motors. The feed rollers are positioned within inches of the chipping knives, effectively controlling even the wildest trees and branches. This reduces trimming time and labor costs while increasing production.

Excels at Chipping Large Diameter Materials

The large 37" diameter drum allows much of the material to be chipped on the bottom half of the drum, with the grain of the wood like a discstyle chipper. The material is chipped using less energy and with less vibration, maximizing fuel economy and reducing maintenance. The large chipper opening and sloped infeed system makes it easy to feed large logs, branches or smaller whole trees into the chipper.

Approximately 30% More Fuel Efficient

The chipper drum in the Intimidator 15XP turns at a slower RPM and has more torque. The synchronized feed system never underfeeds the drum or forces material against it. The chip discharge system includes deep knife pockets, a smooth transition / discharge chute and the patented Power Slot, discharging chips while using much less energy. This also significantly reduces idle time due to the more productive chipper infeed system. These features translate to a fuel savings of approximately 30%.

Significantly Less Maintenance

The Intimidator 15XP has a heavy, reinforced drum with internal baffles. The chipper drum and shaft should last the lifetime of the chipper and are backed by a five-year GUTS warranty. Rugged construction and heavy-duty components throughout the Intimidator 15XP help ensure long life and trouble-free performance. We realize what it costs when a chipper is down, and though we can't eliminate all downtime, we do our best to minimize it.

Higher Quality Chips Per Load

The Intimidator 15XP throws chips with more force due to the pocket design, the larger drum diameter, smooth transition, smooth discharges and the patented Power Slot. This means more chips per load and fewer trips to the dump site. It also means chips from a Bandit chipper have better uniformity compared to rival machines, commanding higher prices when sold and making them easier to dispose of.

Greater Knife Life

Compared to most competitors the 15XP has double the knives and double the cuts per revolution. Knives in the 15XP do not dull as quickly. Knife maintenance costs, fuel consumption and vibration are all reduced in that you are less likely to operate with dull knives.



6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178







Intimidator™ 15XP **Safety Features**

- Rope/Line Shear Device (standard) Provides an improved chance that rope or lines inadvertently entering the chipper may be cut.
- Last Chance Cables (standard) Stops/reverses the feed wheel when pulled in case of an emergency
- Operator Safety Control Bar (standard) Wraps around three sides of the infeed chute and controls the direction of the feed wheels.
- Wood Pusher Paddle (standard) Used to feed small wood debris into the chipper.
- Chipper Hood Pin w/Padlock (standard) Prevents unauthorized access to the disc or drum.
- Chipper Hood Engine Disable Plug (standard) Prevents engine from being started without the hood pin in place.
- Feed Wheel Engage (option)
 Requires operators to control feed wheel operation via foot pedal.
- Hydraulic Bottom Bump Bar (option) Stops feed wheels via mechanical connection when bumped, diverting hydraulic power away from the feed wheels.

The Bandit Backbone™ Support

The Bandit Backbone is Bandit's commitment to customer service and support. It's always been a cornerstone of Bandit's philosophy, and today that backbone is stronger than ever. If you own a Bandit hand-fed chipperregardless the age, hours, or warranty status — the Bandit Backbone is here to support you.



Popular Options



Gas Engine

Get a powerful 130 or 165 horsepower GM gasoline engine to power the Intimidator 15XP.

Self-Propelled

Available with a track undercarriage, the Intimidator 15XP can be taken directly to the trees.

Hydraulic Winch

This useful option enables the operator to pull large material to the chipper with ease.

Standard & Custom Colors Available

YELLOW

Intimidator™ 15XP **Specifications**

ENGINES

- GM 130 HP Gas
- GM 165 HP Gas
- CAT or Perkins 122.5 HP Tier 4 Final CAT or Perkins 147 HP Tier 4 Final

John Deere 140 HP Tier 3

- CAT or Perkins 122.5 HP Tier 4 Final CAT 142 HP Tier 3
- CAT or Perkins 97 HP Tier 3
- CAT or Perkins 114 HP Tier 3
- CAT or Perkins 114 HP Tier 3
- CAT 142 HP Tier 3

UNDERCARRIAGES

AXLE - Single 8, 10 or 12,000 lb. electric brake axles TIRES - 17.5" and 16" Tires on 8-bolt rims as well as 15" 12 ply multi rib flotation tires.

RUBBER TRACK - CAT 2-speed 305 CR Rubber Track

MEASUREMENTS:

	TOWABLE:	TRACK:
Length: (Infeed Closed)	15' 7"	12' 7"
Length: (Infeed Open)	17' 8"	14' 7"
Width:	6' 6"	8' 1"
Height	8' 8"	9' 4"
Weight:	8,000 lbs	11,500 lbs
Fuel Tank:	25 gal	50 gal
Hyd.Tank:	12 gal	50 gal

OTHER SPECIFICATIONS:

Capacity: Throat Ope 17-¾" x 18-½" **Drum:** 37" diameter x 18-3/4" wide (3/8" thick) Horizontal feed wheels: Displacement (CID): Std. with hand crank swivel

2 Position, 2-1/2" Pintle

8,000 pound "Bulldog" tongue jack, adjustable for height with 15" travel capacity and stationary foot pad

3-Position Manual

