

INTIMIDATOR™ 15XPC

15" Capacity Hand-Fed Chipper

Tree care professionals, municipalities and rental companies seeking a compact-yet-powerful 15" capacity drum chipper turn to the Intimidator 15XPC. This impressive chipper features a 24" diameter chipping drum and at 7,198 lbs. it's easily towable. Built stronger using the highest quality components and assembled with solid welded construction, the Intimidator 15XPC will outperform and outlast all other 15" capacity drum chippers on the market.

COMPACT AND POWERFUL.

- Wide 18.5" x 15" opening for **large limbs**
- **4 knives make twice the cuts** per revolution
- **Fuel efficient** and easy to tow



Big Chipping Power In A More Compact Package

Using Bandit's proven 24" diameter chipping drum with a wide throat opening, the Intimidator 15XPC checks in at approximately 7,198 lbs. The lighter design makes for easier towing, especially in areas where weight restrictions can hamper access or require special licensing for drivers and tow vehicles. Production remains Bandit-strong with gasoline or diesel engine options up to 130 horsepower. Smooth transitions, smooth discharges and the patented Power Slot turn the chipping power into unrivaled throwing power, packing more chips per load for fewer trips to the dump site.

Chip Limby Material With Limited Preparation

The Intimidator 15XPC uses a 24" diameter chipping drum with four knife pockets and a two-wheel Slide Box Feed System, whereas many rival chippers feature drums with only two knife pockets and a single feed wheel. Powerful feed wheel motors provide exceptional pulling and crushing power for material entering the chipper. The feed system on the 15XPC is positioned within inches of the chipper knives, further increasing its effectiveness. These are the reasons why the 15XPC is such an effective chipper – it can process limby brush and trees much faster, with limited hang-ups and little-to-no wood preparation prior to chipping.

Approximately 30% More Fuel Efficient

The chipper drum in the Intimidator 15XPC turns at a slower RPM and has more torque. The result is an increase in fuel economy over rival chippers as well as reduced machine vibration, creating less wear-and-tear on components. The high-flow chip discharge system that gives the 15XPC its throwing power also adds to overall machine efficiency. It's not uncommon for the 15XPC to achieve 30% fuel savings while providing equal or better production compared to rival units.

Significantly Less Maintenance

The Intimidator 15XPC has a heavy, reinforced drum with internal baffles. The drum also chips with four knives that make two cuts per revolution. The chipping drum assembly as well as the Slide Box Feed System should last the lifetime of the chipper and are backed by a five-year GUTS warranty. Rugged construction and heavy-duty components throughout the 15XPC help ensure long life and trouble-free performance.

Greater Knife Life

Compared to most competitors the Intimidator 15XPC has double the knives and double the cuts per revolution. Knives in the 15XPC do not dull as quickly. Knife maintenance costs, fuel consumption and vibration is reduced.



Bandit INDUSTRIES, INC.

6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178

FIND US ONLINE WWW.BANDITCHIPPERS.COM

All specifications, dimensions and options are subject to change without notice, and were current at the time of printing. Dimensions may vary, depending on options and engines selected. Bandit Industries, Inc. reserves the right to change designs, specifications and options without prior notice. © 2017 Bandit Industries, Inc. All Rights Reserved.

CALL YOUR LOCAL BANDIT SALES REPRESENTATIVE TO SCHEDULE A DEMONSTRATION TODAY!

Intimidator™ 15XPC

15" capacity drum-style chipper



Safety Features

- **Rope/Line Shear Device** (standard)
Provides an improved chance that rope or lines inadvertently entering the chipper may be cut.
- **Last Chance Cables** (standard)
Stops/reverses the infeed rollers when pulled in case of an emergency
- **Operator Safety Control Bar** (standard)
Wraps around three sides of the infeed chute and controls the direction of the feed wheels.
- **Wood Pusher Paddle** (standard)
Used to feed small wood debris into the chipper.
- **Chipper Hood Pin w/Padlock** (standard)
Prevents unauthorized access to the disc or drum.
- **Chipper Hood Engine Disable Plug** (standard)
Prevents engine from being started without the hood pin in place.
- **Feed Wheel Engage** (option)
Requires operators to control feed wheel operation via foot pedal.
- **Hydraulic Bottom Bump Bar** (option)
Stops feed wheels via mechanical connection when bumped, diverting hydraulic power away from the feed wheels.

The Bandit Backbone™ Support

The Bandit Backbone™ is Bandit's commitment to customer service and support. It's always been a cornerstone of Bandit's philosophy, and today that backbone is stronger than ever. If you own a Bandit track carrier – regardless the age, hours, or warranty status – the Bandit Backbone is here to support you.



Popular Options



Gas or Diesel Engine Options

Bandit offers a wide variety of gas and diesel engine options to choose from.



Hydraulic Winch

This useful option enables the operator to pull large material to the chipper with ease.

Standard & Custom Colors Available

Choose from six standard colors, or select a custom color to match your fleet.



Intimidator 15XPC™ Specifications

ENGINES

- TOWABLE:**
- GM 130HP Gas
 - CAT and Perkins 122.5 - 142 HP T4 Final
- DIESEL ENGINE OPTIONS (EXPORT ONLY)**
- John Deere 115 HP T3
 - CAT or Perkins 97 - 142 HP T3

UNDERCARRIAGES

- TOWABLE:**
- AXLE** - Single 8,000 lb. Axle
- TIRES** - (2) 215/75R 17.5"

MEASUREMENTS:

- TOWABLE:**
- Length:** 17' 5"
(pan down)
- Length:** 15'
(pan up)
- Width:** 6' 11"
- Height:** 8'
- Weight:** 7,198 lbs.
- Fuel Tank:** 25 Gallons
- Hyd. Tank:** 12 Gallons

OTHER SPECIFICATIONS:

- Capacity:** 15"
- Throat Opening:** 15" x 18.5"
- Drum:** 24" dia. x 18.5" wide (.5" thick)
- RPM:** 1,530
- Feed System:** Slide box
- Adjustable Springs:** 2" - 17"
- Horiz. feed wheels:** (2) 10.625" dia. x 18.75" wide
- Displacement (CCD):** 32.7
- Hydraulic Motors:** 2
- Discharge:** Std. with hand crank swivel
- Deflector:** 3-Position Manual
- Hitch:** 2 Position, 2.5" Pintle
- Frame:** .25" x 2" x 4" main frame
with a .25" x 2.75" x 5.5" tongue
- Lift Cylinder:** Standard
- Tongue Jack:** 8,000 lb. "Bulldog" tongue jack, adjustable for height with 15" travel capacity and stationary foot pad

